

IN THE CLAIMS:

For the Examiner's convenience, the following is a list of all claims included those that have not been amended in the present response to Office Action.

Please replace claims 1, 3, 6, 7, 15-17, 19, 20, 25, 26, 28, 31, 34, 36, 38, 39, 41, 58, 59, 73, 74 and 81-83 with their respective claims as provided below.

Sub E1
D1

1. (twice amended) A method for supporting digital signal processing (DSP) of a plurality of data types, the method comprising:
continuously broadcasting a plurality of firmware algorithms to a plurality of DSP engines; and
selectively monitoring for and receiving at least one firmware algorithm of the plurality of firmware algorithms by at least one of the plurality of DSP engines, wherein the at least one firmware algorithm is used to process data of at least one corresponding data type received by the at least one of the plurality of DSP engines over at least one data line.

Sub E1

2. (once amended) The method of claim 1, further comprising:
receiving at least one pulse coded modulation (PCM) data stream from a public switched telephone network (PSTN);
generating at least one packet of data from the PCM data stream using the received at least one firmware algorithm; and

transmitting the at least one packet of data over an Internet Protocol (IP) network.

D2

3. (twice amended) The method of claim 1, further comprising:
receiving at least one packet of data from an IP network;
generating at least one PCM data stream from the at least one packet of data using the received at least one firmware algorithm; and
transmitting the at least one PCM data stream over a PSTN.

4. (Unchanged) The method of claim 1, wherein the at least one data line comprises at least one bidirectional PCM data stream.

5. (Unchanged) The method of claim 1, wherein the at least one data line comprises at least one bidirectional host bus.

6. (once amended) The method of claim 1, wherein the plurality of firmware algorithms are continuously broadcasted to the plurality of service DSP engines by a master DSP engine resident in a processor.

D3

7. (once amended) The method of claim 6, wherein the plurality of firmware algorithms are continuously broadcasted to the plurality of service DSP engines over a channelized serial bus.

8. (once amended) The method of claim 7, wherein the selectively monitoring for and receiving at least one firmware algorithm comprises:

- determining a data type of the data received into at least one of the plurality of service DSP engines;
- determining at least one firmware algorithm required to process the received data;
- determining an address of at least one channel of the serial bus on which the required at least one firmware algorithm is available.

9. (once amended) The method of claim 8, wherein the selectively monitoring for and receiving at least one firmware algorithm further comprises unmasking a bit of an interrupt mask in the at least one of the plurality of service DSP engines, the unmasked bit corresponding to the address of at least one channel of the serial bus on which the required at least one firmware algorithm is transmitted.

10. (once amended) The method of claim 9, wherein the selectively monitoring for and receiving at least one firmware algorithm further comprises:

- executing at least one interrupt service routine in response to receiving an interrupt signal corresponding to the unmasked interrupt bit;
- receiving the at least one firmware algorithm in response to execution of the interrupt service routine; and

storing the received at least one firmware algorithm in a memory of the service DSP.

11. (unchanged) The method of claim 8, wherein each service DSP memory comprises data correlating each of the plurality of firmware algorithms with a serial bus channel on which each of the plurality of firmware algorithms are transmitted.

12. (unchanged) The method of claim 8, wherein the data correlating each of the plurality of firmware algorithms with a serial bus channel on which each of the plurality of firmware algorithms are transmitted is downloaded to each service DSP engine from the processor.

13. (unchanged) The method of claim 8, wherein the data correlating each of the plurality of firmware algorithms with a serial bus channel on which each of the plurality of firmware algorithms are transmitted is hard-coded in each of the service DSP engines.

14. (unchanged) The method of claim 7, wherein each channel of the channelized serial bus transmits at least one firmware algorithm.

15. (once amended) The method of claim 7, wherein at least one algorithm is transmitted on a channel of the channelized serial bus.

16. (once amended) The method of claim 7, wherein an algorithm is transmitted using at least one channel of the channelized serial bus.

D4
17. (once amended) The method of claim 6, wherein the plurality of firmware algorithms are stored in a memory of the master DSP engine.

18. (unchanged) The method of claim 1, wherein each DSP engine comprises at least one channel.

19. (once amended) The method of claim 1, wherein the continuous broadcast is repetitive.

DS
20. (once amended) The method of claim 1, wherein the plurality of data types comprise modem data, voice data, and facsimile data.

21. (unchanged) The method of claim 1, wherein each of the plurality of DSP engines comprise a memory for storing the at least one firmware algorithm.

22. (unchanged) The method of claim 1, wherein each of the plurality of firmware algorithms are broadcasted using at least one serial block, wherein each of the broadcasted at least one serial blocks comprise a portion of each of the plurality of firmware algorithms.

23. (unchanged) The method of claim 22, wherein the at least one serial block comprises 1024 information bits.

24. (unchanged) The method of claim 22, wherein the broadcast of each of the at least one serial blocks is preceded by a broadcast of an address signal, the address signal identifying the firmware algorithm of the broadcasted at least one serial block.

25. (once amended) An apparatus for supporting digital signal processing (DSP) of a plurality of data types, the apparatus comprising:

a serial bus comprising at least one channel over which a plurality of firmware algorithms are continuously broadcasted; and

D6 a plurality of DSP engines coupled to the serial bus and to at least one data line, at least one of the plurality of DSP engines designed to selectively monitor for and receive at least one firmware algorithm of the plurality of firmware algorithms that are continuously broadcasted, wherein the at least one firmware algorithm is used to process data received by the at least one of the plurality of DSP engines over the at least one data line.

D7 26. (once amended) The apparatus of claim 25, further comprising a master DSP engine resident in a host processor, the master DSP engine coupled to the

D7
serial bus, wherein the master DSP engine continuously broadcasts the plurality of firmware algorithms to the plurality of service DSP engines.

27. (unchanged) The apparatus of claim 26, wherein:

at least one pulse coded modulation (PCM) data stream is received from a public switched telephone network (PSTN);

at least one packet of data is generated from the PCM data stream using the received at least one firmware algorithm; and

the at least one packet of data is transmitted over an Internet Protocol (IP) network.

28. (once amended) The apparatus of claim 25, wherein:

at least one packet of data is received from an IP network;

D8
at least one PCM data stream is generated from the at least one packet of data using the at least one firmware algorithm; and

the at least one PCM data stream is transmitted over a PSTN.

29. (unchanged) The apparatus of claim 25, wherein the at least one data line comprises at least one bidirectional PCM data stream.

30. (unchanged) The apparatus of claim 25, wherein the at least one data line comprises at least one bidirectional host bus.

31. (once amended) The apparatus of claim 25, wherein the plurality of service DSP engines selectively monitor for and receive the at least one firmware algorithm by:

D9 determining a data type of the data received into at least one of the plurality of service DSP engines;

 determining at least one firmware algorithm required to process the received data;

 determining an address of at least one channel of the serial bus on which the required at least one firmware algorithm is available.

32. (unchanged) The apparatus of claim 31, wherein the plurality of service DSP engines selectively monitor for and receive the at least one firmware algorithm by unmasking a bit of an interrupt mask in the at least one of the plurality of service DSP engines, the unmasked bit corresponding to the address of at least one channel of the serial bus on which the required at least one firmware algorithm is transmitted.

33. (unchanged) The apparatus of claim 32, wherein the plurality of service DSP engines selectively monitor for and receive the at least one firmware algorithm by:

 executing at least one interrupt service routine in response to receiving an interrupt signal corresponding to the unmasked interrupt bit;

receiving the at least one firmware algorithm in response to execution of the interrupt service routine; and
storing the received at least one firmware algorithm in a memory of the service DSP.

D10 34. (once amended) The apparatus of claim 31, wherein the data correlating each of the plurality of firmware algorithms with a serial bus channel on which each of the plurality of firmware algorithms are transmitted is downloaded to each service DSP engine from a host processor.

35. (unchanged) The apparatus of claim 25, wherein the data received by the at least one of the plurality of DSP engines comprises at least one channel of multiplexed data received over a public switched telephone network, the data having at least one of the plurality of data types.

D11 36. (once amended) The apparatus of claim 25, wherein the plurality of data types comprise modem data, and facsimile data.

37. (unchanged) The apparatus of claim 25, wherein each DSP engine comprises at least one channel.

D12

38. (once amended) The apparatus of claim 25, wherein at least one algorithm is transmitted on a channel of the serial bus, the serial bus being a channelized serial bus.

39. (once amended) The apparatus of claim 25, wherein an algorithm is transmitted using at least one channel of the serial bus, the serial bus being a channelized serial bus.

40. (unchanged) The apparatus of claim 25, wherein each of the plurality of firmware algorithms are broadcasted using at least one serial block, wherein each of the broadcasted at least one serial blocks comprise a portion of each of the plurality of firmware algorithms, wherein the portion of each of each of the plurality of firmware algorithms comprises 1024 information bits.

41. (once amended) A multiservice digital signal processing (DSP) system comprising:

D13

a processor coupled to at least one data line, the processor comprising a master DSP engine, wherein the at least one data line provides a plurality of data types;

a serial bus coupled to the master DSP engine, the serial bus comprising a plurality of channels over which a plurality of firmware algorithms are continuously broadcasted; and,

D13
a plurality of service DSP engines coupled to the at least one data line and the serial bus, at least one of the plurality of service DSP engines being tailored to selectively monitor for and receive at least one firmware algorithm over the serial bus, wherein the at least one firmware algorithm is used to process data of at least one corresponding data type received by the at least one of the plurality of service DSP engines over the at least one data line.

42. (unchanged) The system of claim 41, wherein:

at least one pulse coded modulation (PCM) data stream is received from a public switched telephone network (PSTN);

at least one packet of data is generated from the PCM data stream using the received at least one firmware algorithm; and

the at least one packet of data is transmitted over an Internet Protocol (IP) network.

43. (unchanged) The system of claim 41, wherein:

at least one packet of data is received from an IP network;

at least one PCM data stream is generated from the at least one packet of data using the at least one firmware algorithm; and

the at least one PCM data stream is transmitted over a PSTN.

44. (unchanged) The system of claim 41, wherein the at least one data line comprises at least one bidirectional PCM data stream.

45. (unchanged) The system of claim 41, wherein the at least one data line comprises at least one bidirectional host bus.

46. (unchanged) The system of claim 41, wherein the plurality of service DSP engines selectively monitor for and receive the at least one firmware algorithm by:

determining a data type of the data received into at least one of the plurality of service DSP engines and determining at least one firmware algorithm required to process the data type;

determining an address of at least one channel of the serial bus on which the required at least one firmware algorithm is available; and

unmasking a bit of an interrupt mask in the at least one of the plurality of service DSP engines, the unmasked bit corresponding to the address of at least one channel of the serial bus on which the required at least one firmware algorithm is transmitted.

47. (unchanged) The system of claim 46, wherein the plurality of service DSP engines selectively monitor for and receive the at least one firmware algorithm by:

executing at least one interrupt service routine in response to receiving an interrupt signal corresponding to the unmasked interrupt bit;

receiving the at least one firmware algorithm in response to execution of the interrupt service routine; and

storing the received at least one firmware algorithm in a memory of the service DSP.

48. (unchanged) The system of claim 46, wherein the data correlating each of the plurality of firmware algorithms with a serial bus channel on which each of the plurality of firmware algorithms are transmitted is downloaded to each service DSP engine from the processor.

49. (unchanged) The system of claim 41, wherein the data received by the at least one of the plurality of DSP engines comprises at least one channel of multiplexed data received over a public switched telephone network, the data having at least one of the plurality of data types comprising modem data, voice data, audio data, and facsimile data.

50. (unchanged) The system of claim 41, wherein each service DSP engine comprises at least one channel.

51. (unchanged) The system of claim 41, wherein at least one algorithm is transmitted on a channel of the serial bus.

52. (unchanged) The system of claim 41, wherein an algorithm is transmitted using at least one channel of the serial bus.

53. (unchanged) The system of claim 41, wherein each of the plurality of firmware algorithms are broadcasted using at least one serial block, wherein each of the broadcasted at least one serial blocks comprise a portion of each of the plurality of firmware algorithms.

54. (once amended) A computer readable medium containing executable instructions which, when executed by a digital signal processor (DSP), cause the DSP to perform a method, the method comprising:

selectively monitoring for and receiving at least one firmware algorithm from amongst a plurality of continuously broadcasted firmware algorithms; and
processing data that has been received from a network with the at least one firmware algorithm.

55. (once amended) The computer readable medium of claim 54, wherein the processing further comprises generating at least one packet of data from a PCM data stream, the PCM data stream corresponding to the data that has been received from a network.

56. (once amended) The computer readable medium of claim 55, wherein the network is a PSTN network.

57. (once amended) The computer readable medium of claim 54, wherein the data that has been received from a network further comprises audio data.

58. (twice amended) The computer readable medium of claim 54, wherein selectively monitoring for and receiving at least one firmware algorithm comprises:

D14 determining a data type of the data that has been received from a network;

determining the at least one firmware algorithm;

determining an address of a broadcast channel where the at least one firmware algorithm is available.

59. (twice amended) The computer readable medium of claim 58, wherein selectively monitoring for and receiving at least one firmware algorithm further comprises unmasking a bit of an interrupt mask, the unmasked bit corresponding to the address

60. (amended) The computer readable medium of claim 59, wherein selectively monitoring for and receiving at least one firmware algorithm further comprises:

executing at least one interrupt service routine in response to receiving an interrupt signal corresponding to the unmasked interrupt bit;

receiving the at least one firmware algorithm in response to execution of the interrupt service routine; and

storing the received at least one firmware algorithm in a memory.

61. (amended) The computer readable medium of claim 54, wherein the data that has been received from a network further comprises voice data.

62. (amended) The computer readable medium of claim 54, wherein the data has been received from a network further comprises facsimile data.

63. (unchanged) The computer readable medium of claim 54 wherein the data that has been received from a network further comprises modem data.

64. (unchanged) The computer readable medium of claim 54 wherein the processing further comprises echo cancellation.

65. (unchanged) The computer readable medium of claim 54 wherein the processing further comprises voice coding.

66. (unchanged) The computer readable medium of claim 54 wherein the processing further comprises suppression of packet bandwidth utilization during voice silence.

67. (unchanged) The computer readable medium of claim 54 wherein the processing further comprises modem relay.

68. (unchanged) The computer readable medium of claim 54 wherein the processing further comprises facsimile relay.

69. (unchanged) A computer readable medium containing executable instructions which, when executed by a digital signal processor (DSP), cause the DSP to perform a method, the method comprising:

selectively monitoring for and receiving at least one firmware algorithm from amongst a plurality of continuously broadcasted firmware algorithms; and
processing data that is to be transmitted over a network with the at least one firmware algorithm.

70. (unchanged) The computer readable medium of claim 69 wherein the processing further comprises:

generating a PCM data stream from at least one packet of data, the PCM data stream corresponding to the data that is to be transmitted over a network.

71. (unchanged) The computer readable medium of claim 70 wherein the network is a PSTN network.

72. (unchanged) The computer readable medium of claim 69, wherein the data that is to be transmitted over a network further comprises audio data.

73. (once amended) The computer readable medium of claim 69, wherein selectively monitoring for and receiving at least one firmware algorithm comprises:

determining at least one firmware algorithm required to process the data that is to be transmitted over the network;

determining an address of a broadcast channel where the required at least one firmware algorithm is available.

74. (once amended) The computer readable medium of claim 73, wherein selectively monitoring for and receiving at least one firmware algorithm further comprises unmasking a bit of an interrupt mask, the unmasked bit corresponding to the address.

75. (unchanged) The computer readable medium of claim 74, wherein selectively monitoring for and receiving at least one firmware algorithm further comprises:

executing at least one interrupt service routine in response to receiving an interrupt signal corresponding to the unmasked interrupt bit;

receiving the at least one firmware algorithm in response to execution of the interrupt service routine; and

storing the received at least one firmware algorithm in a memory.

76. (unchanged) The computer readable medium of claim 69, wherein the data that is to be transmitted over a network further comprises voice data.

77. (unchanged) The computer readable medium of claim 69, wherein the data is to be transmitted over a network further comprises facsimile data.

78. (unchanged) The computer readable medium of claim 69 wherein the data that is to be transmitted over a network further comprises modem data.

79. (unchanged) The computer readable medium of claim 69 wherein the processing further comprises echo cancellation.

80. (unchanged) The computer readable medium of claim 69 wherein the processing further comprises voice coding.

81. (once amended) The computer readable medium of claim 69 wherein the processing further comprises modem relay.

D-16

82. (once amended) The computer readable medium of claim 69 wherein the processing further comprises facsimile relay.

83. (once amended) An apparatus for supporting digital signal processing (DSP), the apparatus comprising:

D16 means for continuously broadcasting a plurality of firmware algorithms to a plurality of DSP engines; and

means for selectively monitoring for and receiving at least one firmware algorithm of the plurality of firmware algorithms by at least one of the plurality of DSP engines, wherein the at least one firmware algorithm is used to process data of at least one corresponding data type received by the at least one of the plurality of DSP engines over at least one data line.

84. (unchanged) The apparatus of claim 83, further comprising:

means for receiving at least one pulse coded modulation (PCM) data stream from a public switched telephone network (PSTN);

means for generating at least one packet of data from the PCM data stream using the received at least one firmware algorithm; and

means for transmitting the at least one packet of data over an Internet Protocol (IP) network.

85. (unchanged) The apparatus of claim 83, further comprising:

means for receiving at least one packet of data from an IP network;
means for generating at least one PCM data stream from the at least one packet of data using the received at least one firmware algorithm; and
means for transmitting the at least one PCM data stream over a PSTN.

86. (unchanged) The apparatus of claim 83 further comprising means for continuously broadcasting the plurality of firmware algorithms.

87. (unchanged) The apparatus of claim 83 wherein the means for selectively monitoring for and receiving at least one firmware algorithm further comprises:

means for determining a data type of the data received into at least one of the plurality of service DSP engines;

means for determining the at least one firmware algorithm;

means for determining an address of at least one broadcast channel where the at least one firmware algorithm is available.

Please add new claims 88 through 114 as provided below.

D-17
88. (new) The method of claim 87, wherein the means for selectively monitoring for and receiving at least one firmware algorithm further comprises means for unmasking a bit of an interrupt mask in the at least one of the plurality of service DSP engines, the unmasked bit corresponding to the address.

89. (new) The method of claim 88, wherein the means for selectively monitoring for and receiving at least one firmware algorithm further comprises:

means for executing at least one interrupt service routine in response to receiving an interrupt signal corresponding to the unmasked interrupt bit;

means for receiving the at least one firmware algorithm in response to execution of the interrupt service routine; and

means for storing the received at least one firmware algorithm in a memory of the service DSP.

90. (new) A method, comprising:

selecting a software routine from amongst a plurality of continuously broadcasted software routines that are each capable of being executed by a Digital Signal Processor (DSP); and

processing data that has been received from a network by executing the software routine upon the DSP.

91. (new) The method of claim 90 wherein the processing further comprises generating at least one packet of data from a PCM data stream, the PCM data stream corresponding to the data that has been received from a network.

92. (new) The method of claim 91 wherein the network is a PSTN network.

93. (new) The method of claim 91 wherein the data further comprises voice or audio data.

94. (new) The method of claim 90 wherein the selecting further comprises:
determining a data type for the data;
recognizing that the software routine can be used to process data having the data type;
determining where the software routine resides amongst the continuously broadcasted software routines.

95. (new) The method of claim 90 wherein the data further comprises voice data.

96. (new) The method of claim 90 wherein the data further comprises facsimile data.

97. (new) The method of claim 90 wherein the data further comprises modem data.

98. (new) The method of claim 90 wherein the processing further comprises echo cancellation.

99. (new) The method of claim 90 wherein the processing further comprises voice coding.

100. (new) The method of claim 90 wherein the processing further comprises suppression of packet bandwidth utilization during voice silence.

101. (new) The method of claim 90 wherein the processing further comprises modem relay.

102. (new) The method of claim 90 wherein the processing further comprises facsimile relay.

103. (new) A method, comprising:

selecting a software routine from amongst a plurality of continuously broadcasted software routines that are each capable of being executed by a Digital Signal Processor (DSP); and

processing data that is to be transmitted over a network by executing the software routine upon the DSP.

104. (new) The method of claim 103 further comprising:

generating a PCM data stream from at least one packet of data, the PCM data stream corresponding to the data that is to be transmitted over a network.

105. (new) The method of claim 104 wherein the network is a PSTN network.

106. (new) The method of claim 104 wherein the data that is to be transmitted over a network further comprises voice or audio data.

107. (new) The method of claim 103 where the selecting further comprises:
recognizing that the software routine is required to process the data;
determining where the software routine resides amongst the continuously
broadcasted software routines.

108. (new) The method of claim 103 wherein the data further comprises voice data.

109. (new) The method of claim 103 wherein the data comprises facsimile data.

110. (new) The method of claim 103 wherein the data further comprises modem data.

111. (new) The method of claim 103 wherein the processing further comprises echo cancellation.

112. (new) The method of claim 103 wherein the processing further comprises voice coding.

113. (new) The method of claim 103 wherein the processing further comprises modem relay.

114. (new) The method of claim 103 wherein the processing further comprises facsimile relay.

D17